

GLASS PASSIVATED SINGLE-OHASE BPIDGE RECTIFIER

GBPC4005 THRU GBPC4010


VOLTAGE RANGE **50 to 1000 Volts**
CURRENT **40.0 Amperes**

FEATURES

- Plastic package has UL flammability classification 94V-0
- Integrally molded heatsink provides very low thermal resistance for maximum heat dissipation
- High forward surge capacity
- Glass passivated chip junction
- High isolation voltage from case to lugs
- High temperature soldering guaranteed: 260°C/10 seconds,

MECHANICAL DATA

- Case: Epoxy, Molded Plastic with integrally mounted heatsink
- Terminals: Plated 0.25" (6.35mm) lug
- Polarity: Polarity symbols marked on case
- Mounting: Thru hole for #10 screw, 20 in-lbs Torque max.
- Weight: 0.62 ounce, 17.5 gram



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

- Ratings at 25°C ambient temperature unless otherwise specified
- Single Phase, half wave, 60Hz, resistive or inductive load
- For capacitive load derate current by 20%

	SYMBOLS	GBPC 40005	GBPC 4001	GBPC 4002	GBPC 4004	GBPC 4006	GBPC 4008	GBPC 4010	UNIT
Maximum Repetitive Peak Reverse Voltage	V_{RRM}	50	100	200	400	600	800	1000	Volts
Maximum RMS Voltage	V_{RMS}	35	70	140	280	420	560	700	Volts
Maximum DC Blocking Voltage	V_{DC}	50	100	200	400	600	800	1000	Volts
Maximum Average Forward Rectified Current At $T_C=55^\circ\text{C}$ (SEE FIG.1)	$I_{(AV)}$	35							Amps
Peak Forward Surge Current 8.3ms single half sine wave superimposed on rated load (JEDEC method)	I_{FSM}	300							Amps
Rating for Fusing ($t < 8.3\text{ms}$)	I^2t	660							A^2s
Maximum Instantaneous Forward Voltage drop Per Bridge element 20.0A	V_F	1.1							Volts
Maximum DC Reverse Current at rated DC blocking Voltage per element	$T_A = 25^\circ\text{C}$	5.0							μA
	$T_A = 125^\circ\text{C}$	500							
Isolation Voltage from case to lug	V_{ISO}	2500							Volts
Typical Thermal Resistance (Note 1 and 2)	$R_{\theta JC}$	1.4							$^\circ\text{C}/\text{W}$
Operating Junction Temperature	T_J	(-55 to +150)							$^\circ\text{C}$
Storage Temperature Range	T_{STG}	(-55 to +150)							$^\circ\text{C}$

- Notes:**
1. Unit mounted on 9" x 3.5" x 4.6" (23cm x 9cm x 11.8cm) AL Plate.
 2. Bolt down on heat-sink with silicon thermal compound between bridge and mounting surface for maximum heat transfer efficiency with #10 screw

GLASS PASSIVATED SINGLE-PHASE BRIDGE RECTIFIER

GBPC4005 THRU GBPC4010

VOLTAGE RANGE 50 to 1000 Volts
CURRENT 40.0 Amperes

RATINGS AND CHARACTERISTICS CURVES GBPC40005 THRU GBPC4010





FIG. 3 - TYPICAL FORWARD CHARACTERISTICS PER BRIDGE ELEMENT




FIG. 4 - TYPICAL REVERSE CHARACTERISTICS PER BRIDGE ELEMENT




FIG. 5 - MAXIMUM POWER DISSIPATION

